

1120nm CW Single Mode Fiber Laser



2024 V1

For customized projects please Contact us:

info@simtrum.com

The **1120nm CW Single Mode Fiber Laser** features a semiconductor laser chip, expertly engineered drive circuit, and TEC control, ensuring safe laser operation, consistent output power, and spectral stability.

Ideal as a seed laser for high-power applications, it also serves well in production testing of optical fiber devices in the 1120nm range. Available in both benchtop and modular formats, this laser provides a narrow spectral width and exceptional long-term stability, essential for precision and reliability in high-accuracy applications.



Features

- High Output Power
- Power And Spectral Stability
- Single Mode Or Biased Output

Applications

- High Power Laser
- Fiber Lasers
- Optical Fiber Device Testing

Specifications

Optical Parameters	Unit	Typical Value	Remarks
Wavelength	nm	1120±1	
Spectral Width	nm	≤0.1	@3dB
Output Power	W	1/2/5	
Short-term Stability (15 minutes)	dB	±0.02	
Long-term Stability (8 hours)	dB	±0.05	
Pigtail Type	—	Hi1060 Single Mode	PM980 Polarization-Maintaining Output Models Are Available
Pigtail Connector Type	—	FC/APC	

General Parameters	Table Model	Module
Control Mode	Keystroke	RS232 Serial Port Communication
Communication Interface	* Optional	DB9 Female
Power Supply	100~240V AC, <30W	5V DC, <15W
Size	260(W)×280(D)×120(H)mm	125(W)×150(D)×20(H)mm
Operating Temperature Range	-5~+55°C	
Operating Humidity Range	0~70%	

Ordering Information/Model Number				
Series	Wavelength(nm)	Output Power (W)	Fiber	Packaging
STFLH	1120	1/2/5	SM= HI 1060	M=Module B=Table Model
			PM= PM 980	

Test Data

