


AOM Specifications 声光调制器产品规格书

STM0028-QL200-035-266



1. SPECIFICATIONS (规格)

Interaction material (介质材料)	Crystal quartz (石英)
Acoustic mode (声波模式)	Longitudinal (纵波)
Operating wavelength (工作波长)	266nm
Polarization (光偏振)	Linear, vertical to base (线偏振, 垂直于基座)
Transmission (透过率)	> 90%
Active aperture (有效孔径)	3.5mm
Center frequency (Fc) (中心频率)	200MHz
Diffraction efficiency (衍射效率)	> 85%
RF power (射频功率)	10 W (max)
Input Impedance (输入阻抗)	50Ω Nominal
VSWR (驻波比) @Fc	< 1.2:1
RF connector (射频接头)	SMA-F
Cooling (散热方式)	Conduction-cooled (传导散热)
Shell material (外壳材料)	Aluminum alloy 6063 (铝6063)
Storage temperature (存储温度)	-20~70 °C

2. PERFORMANCE vs. WAVELENGTH (性能 vs. 波长)

Wavelength (光波长) -um	266
Bragg angle (布拉格角) -mrad	4.6
Separation angle (分离角) -mrad	9.3


3. ESTIMATED PERFORMANCE vs. BEAM DIAMETER (预估性能 vs. 光束直径)

Beam diameter (光束直径) -mm	1	2	3
Rise time (上升沿时间) -ns	113	226	339
Diffraction efficiency (衍射效率) @Fc	85%	85%	85%

4. ORDERING CODES (编码规则)

	Fc	Active aperture	Wavelength
STM0001—	QLXXX	— XXX	— XXXX
27.12 MHz	027	040 4 mm	9400 9.4 μ m
40.68 MHz	041	060 6 mm	10600 10.6 μ m
80 MHz	080	080 8 mm	

5. DIMENSIONS (外形尺寸-mm)



6. SUGGESTED RF DRIVER ELECTRONICS (建议驱动型号)

RD1022-200-24-015-CA

7. REVISION (版本)

Number (版本号)	Revisions date (修订日期)	Revision (修改项目)	Revision description (修订内容说明)
A	2023.6.25	New	/

Quality Assured: In house made, high damage threshold, Vacuum bonding, 100% Diffraction efficiency test & burn-in test.