

REDEYE

NIR Hyperspectral Imaging Camera

The new **RedEye** is a linescan (pushbroom) hyperspectral imaging camera in the near-infrared spectral range that allows the acquisition of real-time data with high spectral and spatial resolution.

This new capability was developed from our vast experience with industrial applications we have delivered in the past decade.

Combining a superior optical design with an advanced 3-D transmission grating technology, high-end electronics, and a fast FPA detector, the **RedEye** camera provides an outstanding performance even under harsh environmental conditions.

inno-spec's new approach of material characterization allows reliable measurements combining chemical and spatial information. It therefore enables comprehensive analytical applications for the laboratory or for critical online or in-line monitoring in manufacturing processes.

To meet different user demands, multiple software packages are available: from hardware drivers through laboratory software up to fully automated real-time routines for rapid data acquisition, evaluation, and process control.

NEW



Features

- Transmission grating configuration for superior sensitivity
- High spatial and spectral resolution
- High frame rate
- Excellent imaging performance
- Robust design



Technical Specifications:

RedEye 1.7 - NEW RedEye 2.2

Spectrograph

Spectral range typ. 950 to 1700 nm typ. 1200 to 2200 nm Dispersion 106 nm/mm 140 nm/mm Spectral resolution 10 nm (with 80 um slit) 13 nm (with 80 um slit) Spatial resolution rms spot radius < 35 μm rms spot radius <85 µm Smile < 60 µm $< 75 \mu m$ Keystone $< 50 \mu m$ $< 25 \mu m$ F-number 2.6 2.6 Slit width (default) 80 µm 80 µm

Electronics

Sensor InGaAs extended InGaAs Pixels in full frame 320 x 256 320 x 256 Pixel size 30 x 30 µm 30 x 30 µm Bit depth 13 bit 14 bit 330 fps (full frame) 330 fps (full frame) Frame rate 4200 fps (4 bands) Data interface Gigabit Ethernet Gigabit Ethernet (GigE Vision standard) Camera control Ethernet RS 485 Power supply 12 - 36 V DC 24 V DC 1-Stage TEC 2-Stage TEC Cooling

Operating Conditions

Temperature $-5^{\circ}\text{C} \text{ to } + 40^{\circ}\text{C}$ $-5^{\circ}\text{C} \text{ to } + 40^{\circ}\text{C}$

Mechanics

Dimensions I x w x h 368 x 130 x 145 mm³ 400 x 184 x 180 mm³ Weight 4.3 kg 10.5 kg
Lens mount Standard C-mount Standard C-mount Protection type IP65, IP67

Please note that any specs on the datasheet are subject to change without notice.

Optionally, by replacing the input optics with a multifiber cable, the **RedEye** can be used as a synchronous multipoint, multichannel spectrometer.

As a well-established manufacturer of spectroscopic measurement equipment, **inno-spec** provides optimized solutions for any individual application: from customized OEM components for system suppliers up to fully integrated turnkey solutions for the end-user.

Accessories

- Tungsten halogen light sources in modular sizes
- Different fore optics:
 8 mm, 16 mm, 25 mm,
 35 mm, 50 mm
- Numerous software packages
- Multifiber bundle (up to 66 channels)

